In the Claims

Claims 5, 10-12, 14 and 21 are amended.

Claims 1-25 remain in the application and are listed below:

1.   (Previously Presented) A method comprising:

receiving a command from a decoder application at an application program interface (API), wherein the API is configured to facilitate the use of a plurality of different multimedia accelerators with the decoder application; and

generating one or more filter control command data structures, recognizable by a communicatively coupled accelerator including one or more parameters which, when received by the accelerator, affects one or more filter settings of the accelerator based, at least in part, on the content of the received command.

2.   (Original) A method according to claim 1, further comprising:

passing the generated filter control command data structures to the accelerator, wherein the accelerator modifies one or more filter settings in accordance with the parameters embedded within the data structure.

3.   (Original) A method according to claim 1, wherein the filter is a post-processing filter.

4.   (Original) A method according to claim 3, wherein output data subsequent to the application of a post-processing filter are used as prediction references for decoding subsequent data.

5. (Currently Amended) A method according to claim 3, wherein the post-processing filter is one or more of a deblocking filter[[,]] and a de-ringing filter, and the like.

6. (Original) A method according to claim 1, wherein the parameters include a strength parameter.

7. (Original) A method according to claim 6, wherein the generated data structure includes a strength parameter for each of one or more block boundaries of a frame.

8. (Original) A method according to claim 1, wherein the API issues filter control commands for each of a number of edges of luminance and chrominance blocks of received media content.

9. (Original) A method according to claim 1, wherein the API issues macroblock filter control command data structures for each macroblock of video picture content, each macroblock filter control command comprising four (4) or sixteen (16) luminance block filter control command data structures for controlling the filtering of the luminance blocks of the macroblock, and/or two (2), four (4), eight (8), sixteen (16), or thirty-two (32) chrominance block filter control command data structures for controlling the filtering of the chrominance blocks of the macroblock.

10.   (Currently Amended) ~~A storage medium comprising a plurality of executable instructions which, when executed~~ One or more computer-readable media having computer-readable instructions stored thereon which, when executed by a computer, implement a method according to claim 1.

11.   (Currently Amended) A ~~computing~~ system comprising:

a ~~storage medium having stored therein a plurality of executable instructions~~ one or more computer-readable media; and

an ~~execution unit, coupled to the storage medium, to execute at least a subset of the plurality of executable instructions to~~ computer-readable instructions on the one or more computer-readable media which, when executed by one or more processors, implement a method according to claim 1.

12.   (Currently Amended) ~~A storage medium comprising a plurality of executable instructions which, when executed~~ One or more computer-readable media having computer-readable instructions stored thereon which, when executed by a computer, implement an application program interface (API) to dynamically generate one or more filter control command data structures in response to a command received from a decoder application, wherein the one or more filter control command data structure(s) include one or more parameters which, when received by a communicatively coupled accelerator, effect one or more filter settings on the accelerator in accordance with the received command, wherein the API is not specific to any particular multimedia application and/or multimedia accelerator.

13.   (Original) A storage medium according to claim 12, wherein the filter control command data structure(s) effect one or more post processing filter(s) of the accelerator.

14.   (Currently Amended) A storage medium according to claim 12, wherein the filter control command data structure(s) effect one or more of a deblocking filter(s), de-ringing filter(s), and/or another post processing filter of the accelerator.

15.   (Original) A storage medium according to claim 12, wherein the API issues a filter control command data structure for each of a number of edges of luminance and chrominance blocks of received media content.

16.   (Original) A storage medium according to claim 15, wherein the API issues four (4) filter control command data structures for each luminance block, and/or two (2) filter control command data structure(s) for each chrominance block.

17.   (Original) A storage medium according to claim 12, wherein the parameter(s) include a filter strength parameter.

18.   (Previously Presented) A computing system comprising:
a decoder application to process received media content; and
an operating system including an application program interface (API),
support the media processing, wherein the API generates one or more filter control

commands including one or more parameters which, when received by a communicatively coupled media processing accelerator, effect one or more filter settings of the accelerator in accordance with a command received from the decoder, wherein the decoder application is configured to iteratively issue configuration commands reflecting various alternative degrees and methods of decoding acceleration capability until choosing one that is acceptable to both the decoder application and the accelerator.

19.   (Original) A computing system according to claim 18, further comprising:

one or more media processing accelerator(s), communicatively coupled to the decoder application via the API, including one or more filter(s) responsive to the filter control command data structures reflecting information received in the command from the decoder.

20.   (Original) A computing system according to claim 19, wherein the filter(s) are post processing filters.

21.   (Currently Amended) A computing system according to claim 19, wherein the filter(s) include one or more of a deblocking filter[[,]]and de-ringing filter, and the like.

22. (Original) A computing system according to claim 18, wherein the API issues macroblock filter control command data structures for each macroblock of video picture content, each macroblock filter control command comprising four (4) or sixteen (16) luminance block filter control command data structures for controlling the filtering of the luminance blocks of the macroblock, and/or two (2), four (4), eight (8) , sixteen (16) or thirty-two (32) chrominance block filter control command data structures for controlling the filtering of the chrominance blocks of the macroblock.

23. (Original) A computing system according to claim 18, wherein the filter control command data structures include a strength parameter to control an amount of filter applied by a receiving filter.

24. (Original) A computing system according to claim 18, further comprising:

a storage medium having stored therein a plurality of executable instructions; and

an execution unit, coupled to the storage medium, to execute at least a subset of the plurality of executable instructions to implement the operating system and associated API.

25. (Original) A computing system according to claim 24, wherein the execution unit executes at least a subset of the plurality of executable instructions to implement the decoder application.